



8p 10 /100M Switch with 4p 802.3at/af PoE **PS804**



Features

- No need for setting and comply with IEEE 802.3at/af PoE standard
- Remote PoE PD Detection
- 11" Metal Case
- Holders to 19" Cabinet for Rack Mounted (optional)
- Auto-MDI/MDI-X, Auto-Negotiation
- Non-Blocking
- Internal Power Supply

Specifications

Standard

- IEEE 802.3 10BaseT
- IEEE 802.3u 100BaseTX
- IEEE 802.3x Full-duplex and Flow Control
- IEEE 802.3at/af Power over Ethernet

Environmental Specification:

- Operating Temperature
 - 0 to 40 °C
- Storage Temperature
 - -20 to 90 °C
- Humidity
 - 10 to 90% RH (non-condensing)

Number of Port

- 8-port 10/100BaseT(X) with 4-port PoE

Mechanical:

- LED Indicator
 - Per Port: Link / Act, PoE
 - PoE Port: Act / Status
 - Per Unit: Power
- Power Consumption
 - 65 Watts
- Power Supply
 - 100~240V/AC, 50~60Hz
- Power Output
 - 54V/DC per Port Output – 30 W Max per Port
- Product Dimensions / Weight
 - 280 x 180 x 44 mm (L x W x H)/ 1.6kg

Box Dimension

- 295 x 240 x 65 mm (L x W x H)

<p>Performance:</p> <ul style="list-style-type: none"> • MAC Address: 1K • Buffer Memory: 64KB • Transmission Method: Store and Forward 	<p>Accessory</p> <ul style="list-style-type: none"> • Power Cord • User Manual • Rack-mount Holders (Optional)
<p>Carton Dimension</p> <ul style="list-style-type: none"> • 440 x 400 x 270 mm : 5 pcs/per carton 	<p>N.W / G.W</p> <ul style="list-style-type: none"> • 11 kg / 12 kg
<p>Certification</p> <p>FCC, CE, LVD</p>	

Application Diagram



Ordering Information

PS804 • 8-port 10/100M Fast Ethernet Switch with 4-port 802.3at/af PoE, 65w internal power

Yoda Communications, Inc. www.yoda.com.tw

2F, No. 3-1, Industry East Road IX, Science Based Industrial Park, HsinChu, Taiwan

Tel:+886-3-563-2323 Fax:+886-3-563-6420