

10-Port GbE Switch with 8-port 802.3at PoE, 2-port SFP PS820G



PS820G series, a 10-port Gigabit PoE+ Switch, is a standard Gigabit Ethernet switch that meets all IEEE 802.3/u/x/z/ab/af/at standards. The switch includes 8-Port 10/100/1000Mbps RJ-45 with PoE+ function and 2-Port Gigabit SFP for Fiber. It is an ideal solution for applications of wireless AP, IP phones and IP cameras.

Key features

- 8 x RJ-45 ports for Gigabit Ethernet connection with PoE+ capacity
- 2 x SFP ports flexible for fiber connection
- Support Jumbo Frame size up to 9KB
- IEEE802.3at/af Power Over Ethernet
- Plug and play for easy configuration

Technical Specifications

- Standard compliance
 - IEEE 802.3 10Base-T Ethernet

Yoda Communications, Inc. www.yoda.com.tw

2F, No. 3-1, Industry East Road IX, Science Based Industrial Park, HsinChu, Taiwan

Tel:+886-3-563-2323 Fax:+886-3-563-6420



- IEEE 802.3u 100Base-TX Fast Ethernet
- IEEE 802.3ab 1000Base-T Ethernet
- IEEE 802.3z 1000Base-X Ethernet
- IEEE 802.3x Flow Control capability
- IEEE 802.3at/af

RoHS Compliance

Performance

Switching capacity:

- 8 Gigabit Ethernet ports with non-blocking wise speed performance.
- 16Gbps switch capacity
- 8 K MAC addresses
- Supports Jumbo frame, up to 9K

■ PoE Features

- 8 x IEEE802.3at/af PoE+ PSE ports
- Endpoint with 54VDC power through RJ-45 pin 1, 2, 3, 6
- PoE-PSE activity LED indicator
- Auto detect powered device
- 120 or 250 watts of total power selected

LED Descriptions

LED Description

LED	Color Function	
System LED		
PWR	Green	Lit when +5V power is coming up

Yoda Communications, Inc. www.yoda.com.tw

2F, No. 3-1, Industry East Road IX, Science Based Industrial Park, HsinChu, Taiwan



10/100/1000 Ethernet TP Port 1 to 8 LED				
LAN	Green/	Lit Green when TP link on 1000Mbps speed		
	Amber	Lit Amber when TP link on 10/100Mbps speed		
		Blinks when any traffic is present		
PoE	Green	Lit when PoE Power is active		
1000SX/LX Gigabit Fiber Port 9, 10 LED				
LAN	Green	Lit when connection with the remote device is good		
		Blinks when any traffic is present		
		Off when module connection is not available		

Network Interface

	Connector	Port
10/100/1000Mbps TP Jack (RJ-	TP(RJ-45)	1 to 8
45)		
1000Mbps SFP Fiber Module	SFP	9, 10
Auto Detection		

■ Hardware Spec.

Feature		Detailed Description
	Voltage	: 100~240 V
Power Characteristics	Frequer	ncy : 50~60 Hz
	PoE Power	Max. 120W (PS820G)
		Max. 250W (PS820GA)
Ambient Temperature	0° to 40°	C
Humidity	5% to 90	0%
Dimensions	44(H) x 280(W) x 215(D)mm	
Weight	2.3kgs	

Yoda Communications, Inc. www.yoda.com.tw



	FCC Part 15 Class B, CE
EMI	

Ordering Information

PS820GA	10-Port GbE Switch with 8-Port PoE+ and 2-port SFP (Internal Power of 250W)
PS820G	10-Port GbE Switch with 8-Port PoE+ and 2-port SFP (Internal Power Module of 120W)
PS820GL	10-Port GbE Switch with 8-Port PoE+ and 2-port SFP (Internal Power Module of 65W)