

FXS/FXO VoIP Router

4/8 port
VoIP Router

Connect Port

- 4/8 x RJ-11 FXS or FXO ports
- 2 x RJ-45 10/100Mbps WAN Ethernet Ports
- 2 x RJ-45 10/100Mbps LAN Ethernet Ports

Voice Processing

- Audio CODEC:
 - G.711 A-law / u-law
 - G.723.1
 - G.726
 - G.729a/G.729b
- Support T.38 / T.30 FAX Relay
- Carrier tone detection and generation
- Silence suppression and comfort noise
- DTMF In/Out band Relay
- DTMF/ Call progress detection and generation
 - Q.931 Fast Start
 - Support Caller ID generation and detection
 - Support VAD, H.225, H.245, CNG, G.168, Jitter buffer and programmable gain control

Voice Signaling

- Support SIP VoIP calls
- Support SIP v2 Standard (RFC3261)
- NAT Traversal
 - Outbound Proxy
 - STUN Server
- Register up to 4 Server simultaneously
- Support multiple dialing plan / Call hunting group
- Adaptive Jitter Buffer Function
- Support multiple dialing plan / Call hunting group
- Extensible by external IVR/CDR/Billing server for value-added application
- Support current drop and polarity reversal detection and generation on analog trunk interface
- Selectable group or sequence ring the PBX when VoIP call in
- IP screening table for authorized VoIP call in
- Flexible Routing table and profile

Management

- Web Interface Management
- Support Auto Provision Server
- Remotely configuration/Upgrade by Web UI or Auto Provision Server.
- Exportable CDR to CDR server
- 1 Reset button for load default ID/Password.
- WAN IP configure can be programmed by phone with IVR prompt
- Build-in watching dog for auto recovery

Router Functions

- Support static & dynamic IP from DHCP, PPPoE
- Build-in DHCP Server and Client
- Support NAT through function
- Supported Protocol: UDP, TCP, NAT, BOOTP, TFTP, FTP, HTTP, TELNET, IEEE 802.3/ IEEE 802.3u
- Support SNMP, SNTIP, HTTP, FTP, NAT, DNS, uPnP, DDNS
- NAT function: Virtual Server, Port mapping, Static routing table
- Firewall option: Client filtering, URL filtering, MAC control, Drop Port scans
- Support QoS (ToS& DSCP) and bandwidth control, reserve bandwidth for VoIP call when data traffic busy.

Hardware Specification

- LED Indicators: READY, STATUS, POWER, WAN, LAN, PHONE and LINE.
- Power: AC100V-240V, DC 12V/2A (Max)
- Temperature: 0° C to 45° C (Operation), -20° C to 75° C (Storage)
- Humidity: up to 90% non-condensing
- Dimension: 240 x 163 x 53 mm (W/D/H)
- Weight: 636g

Emissions

- CE Mark

Warranty

- One Year Limited Warranty

VA404/440/808/880 4/8 channel VoIP/PSTN smart call router series:

- IP/PSTN Dual Access –Incoming and outgoing calls from both IP and PSTN networks use same POTS phone set.
- Dual FXO/FXS interface for connect between PBX and PSTN
- Smart routing select between VoIP and PSTN by prefix number
- Automatic reroute the call via PSTN when VoIP failure with warning sound
- Maintain the call by bypass relay when power failure
- Direct analog bypass route when call between Line and Phone
- Support call waiting notice

4/8 port Dual FXO/FXS Interface!

VA404/440/808/880 have 4/8 port Dual PSTN/FXS interface to connect between PBX and PSTN!

Life line support! (FXS+PSTN Mode)

Automatic reroute the call via PSTN when VoIP failure with warning sound or power off bypass.

SIP support!

Deploy into any multimedia, interactive, or softswitch network with the leading call and session signaling protocol

Register up to 4 SIP Platforms mixable simultaneously!

Flexible registration for different VoIP Route plan

Firewall, NAT, DHCP, PPPoE

Connect to any broadband or access provider, serve the whole network, and secure your data. User configurable IP services ensure every host is connected to the LAN.

Auto-Provision-Server Support!

Easy to remote configure/Upgrade via Auto Provision Server.

WAN/LAN IP Setting by Phone

Easy IP configuration by Phone

QoS guaranteed Voice package

Quality of Service ensure voice traffic gets high priority without shutting down your Ethernet LAN

Bandwidth control

users can manage the limitation of network bandwidth and prioritize VoIP packet to pass through, also voice quality and communication stability are totally enhanced.



Model Information

- VA440: 4FXS
- VA404: 4FXO

- VA880: 8FXS
- VA808: 8FXO